

# Architectural Surfaces, Inc.

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
952-448-5300 • Fax: 952-448-2613 • Toll Free: 1-800-448-3134

# WOODGRILLE™

---

---

## WOODGRILLE™ – SPECIFICATIONS

ARCHITECTURAL SURFACES, INC. 952-448-5300

### Section 13020 Special Wood Rail Ceiling System

#### Part 1: General

##### 1.1 Scope:

- A)** The work in this section shall be subject to the requirements of the General Conditions.
- B)** Work Included: Furnish all labor, materials, equipment and services required in conjunction with the installation of the wood rail ceiling system specified herein and identified on the drawings and schedules including:
  - 1) Suspension system.
  - 2) Wood rail ceiling panels.
  - 3) All factory applied and/or field installed accessories, wood moldings or trim relating to the ceiling system.
  - 4) Integrated air diffusion (optional).
  - 5) Acoustical Insulation (optional).
  - 6) Factory prefinishing (optional).
- C)** Related work specified elsewhere:
  - 1) Painting or finishing (optional).
  - 2) Acoustical work.
  - 3) Mechanical connections to integrated air components (optional).
  - 4) Balancing of air distribution system (optional).
  - 5) Millwork.


##### 1.2 Quality Assurance:

- A)** Manufacturer: The manufacturer shall have completed at least five projects of the scope and quality required by this project.
  - 1) The manufacturer shall supply extra backing strips to be applied to the back of the panel ends, when field cut, to prevent warping or twisting in the rails and provide the highest quality in appearance.
- B)** Contract Execution: The bidding subcontractors shall be approved by the manufacturer's local distributor/representative of the specified materials and shall be thoroughly experienced in this type of work.









# Architectural Surfaces, Inc.

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
952-448-5300 • Fax: 952-448-2613 • Toll Free: 1 -800-448-3134

# WOODGRILLE™

## WOODGRILLE™

### INSTALLATION RECOMMENDATIONS & INSTRUCTIONS

***CAUTION: Do Not Install Until Instructions Have Been Read Completely.***

#### WARNING:

All solid wood products are cellular and are subject to expansion, contraction, or warping. Under normal construction conditions, wood can expand or contract up to 1/8th of an inch per foot. Panels **should not** be subject to high or low humidity, storage, should preferably be between 40 and 50 percent relative humidity. Storage, even for a short period of time, in areas where the humidity is over 60 or under 30 percent could cause permanent damage to the panels. (See Job Conditions). The manufacturer assumes no liability for expansion, contraction, or warping of louvers that may have been exposed to extreme conditions. For the best installation results these instruction must be followed exactly.

#### RECEIVING:

Check cartons for any obvious shipping damage to the panels; if you feel there is concealed damage, open cartons and inspect. Have driver sign for any damaged panels and the consignee shall file a freight claim with the carrier at once. **The manufacturer assumes no responsibility for filing freight claims or for shortages.**

Make sure that all of the material ordered for the job has been received and is the proper style or styles and in the proper quantities.

If any panel appears to have manufacturing defects, do not install. The manufacturer's only obligation is replacing materials proven to be defective and that are returned for credit, within the terms and conditions of the sale. Notify the manufacturer or distributor/representative at once.

#### STORAGE:

Panels shall be stored in a flat horizontal position on wood blocking not more than 12" o.c.

Protect all panels from exposure to moisture or to light with dark colored polyethylene or similar material. Do not store panels in damp areas or in freshly plastered buildings. Terrazzo grinding must be completed and cement cured. Storage space must be dry and well ventilated.
































# Architectural Surfaces, Inc.

**DISTINCTIVE WOOD & SPECIALTY ACOUSTICAL CEILING & WALL SYSTEMS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
952-448-5300 • Fax: 952-448-2613 • Toll Free: 1-800-710-8791  
e-mail: [info@architecturalsurfaces.net](mailto:info@architecturalsurfaces.net)  
Visit Our Web Site at [www.architecturalsurfaces.net](http://www.architecturalsurfaces.net)


---

---

**CEILING YOU CAN LOOK UP TO!**

## Finishes

**All of our wood systems are available factory pre-finished. Commercial projects typically require solid wood products to be finished with an intumescent Class A fire retardant varnish to meet local fire codes. Standard and catalyzed lacquer finishes are also available that are typically used on veneer faced products that have Class A Fire particle board core. We typically match customers stain samples for color approval.**



# Architectural Surfaces, Inc.

**DISTINCTIVE WOOD & SPECIALTY ACOUSTICAL CEILING & WALL SYSTEMS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
952-448-5300 • Fax: 952-448-2613 • Toll Free: 1-800-710-8791  
e-mail: [info@architecturalsurfaces.net](mailto:info@architecturalsurfaces.net)  
Visit Our Web Site at [www.architecturalsurfaces.net](http://www.architecturalsurfaces.net)


---

---

***CEILINGS YOU CAN LOOK UP TO!***

## **Maintenance/Cleaning**

**Our wood products will require little maintenance. Surfaces may require standard dusting periodically. A feather duster can be used on the Woodcube™ and Woodgrille™ systems. A non-abrasive soft cloth with a light application of “Liquid Gold” applied to the cloth should be used to clean or dust flat panels or linear systems.**



# Architectural Surfaces, Inc.

DISTINCTIVE WOOD & SPECIALTY ACOUSTICAL CEILING & WALL SYSTEMS

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
952-448-5300 • Fax: 952-448-2613 • Toll Free: 1-800-710-8791  
e-mail: [info@architecturalsurfaces.net](mailto:info@architecturalsurfaces.net)  
Visit Our Web Site at [www.architecturalsurfaces.net](http://www.architecturalsurfaces.net)

---

---

*CEILINGS YOU CAN LOOK UP TO!*

## Limited Product Warranty

All wood and wood composite products sold by Architectural Surfaces, Inc. are warranted to be free of defects in workmanship for a period of one year from the date of shipment.

\*No other warranty is expressed or implied. Claims are considered for material only which is supplied by ASI not labor to remove or install. Warranty is subject to the terms and conditions of sale and strict compliance with our recommended procedures for site conditions, receiving, storage and installation.